

MEGA RUBBER GUM

ONE-COMPONENT POLYURETHANE ADHESIVE OR BONDING
SYNTHETIC GRASS SURFACES

TURF PRO

PROFESSIVE PROFESSIVE ADHES SERIES SERIES



DATA SHEET

DESCRIPTION

MEGA RUBBER GUM is a polyurethane resinbased, moisture-curing adhesive. It is produced using technology developed in MAPEI's own laboratories, and has the following characteristics:

- One-component, ready-to-use product; no hardener is required, therefore no preliminary mixing; if stored correctly, remaining quantities of the product may be used again at a later date;
- Easy to apply, even at low temperatures;
- Excellent ridge hold, even in summer at high tempratures.
- Very limited expansion of the product, therefore no flatness problems after laying;
- It does not contain solvents or other substances which give off unpleasant smells.

SPECIFICATIONS:



MEGA RUBBER GUM is a polyurethane resinbased, moisture-curing adhesive. It is produced using technology developed in MAPEI's own laboratories, and has the following characteristics:

- One-component, ready-to-use product; no hardener is required, therefore no preliminary mixing; if stored correctly, remaining quantities of the product may be used again at a later date:
- Easy to apply, even at low temperatures;
- Excellent ridge hold, even in summer at hightemperatures;
- Very limited expansion of the product, therefore no flatness problems after laying;
- It does not contain solvents or other substances which give off unpleasant smells.

AEREA OF APPLICATION:

Preparation of the sub-base

Sub-bases to synthetic playing surfaces must be prepared in accordance with the surface manufactures instructions and the type of use foreseen, and must comply with current regulations and standards.

Acclimatisation

The single sheets must be unrolled a few hours before starting laying operations, and must be spread out to allow internal tensions caused by the packaging to be reduced.



MEGA RUBBER GUM is available in green.

READY FOR USE

The artificial turf surface is ready for service after approximately 7 days if laid as described above.



Property	Value	Test Method
Consistency:	Creamy Paste	*** / .
Colour	Green	
Density (g/cm³):	1.40	
Dry solids content (%):	100	
Recommended application temp	from +0°C to +35°C	
Set to light foot traffic:	approximately 12 hours	
Shear strength (EN 12228- EN 13744):	> 1500 N (std. condition)	
	> 1500 N (after 14 days in water at +70°C)	-
Open time (formation of surface skin):	30 minutes	
Elongation at break (DIN 53504) (%) (7 days at +23°C + 14 days at +50°C):	500%	



Head Office: Plot No. C1-C, 2nd Floor, Plant: Plot B-653, Sector-3, Near Main Khayaban-e-Itehad, Near KFC, Opposite Dubai Islamic Bank, DHA Phase 7, Karachi.

Life Care Medical, Ahsanabad, Karachi.

Contact: +923183880163 | +922135318800 www.megasealers.com | info@megasealers.com