

This product has sealed, protected, and conquered cracks. Stay ahead of the elements with a flexible solution for all your exposed surfaces. Defend against moisture and damage with our reliable crack filler – the ultimate choice for exposed applications.

KEY FEATURES:

Superior Crack Repair:

Mega Crack Fix's advanced formula is designed to effectively repair and seal cracks in concrete structures, preventing further damage and ensuring structural integrity.

Exceptional Durability:

With Mega Crack Fix, you can trust that your concrete repairs will withstand the test of time. This product is engineered to resist cracking, shrinking, and color fading, ensuring your concrete maintains its strength and appearance.

Easy Application with Integrated Nozzle:

Mega Crack Fix features an innovative nozzle applicator that simplifies the repair process. Just place the bottle's nozzle directly over the crack, apply gentle pressure, and watch the solution flow smoothly and evenly into the damaged area.

Suitable for Indoor and Outdoor Use:

Whether you're repairing cracks in interior or exterior concrete structures, Mega Crack Fix provides reliable performance in various environments.

USAGE GUIDELINES:

- 1. Begin by preparing the cracked area, ensuring it is clean and free from debris.
- 2. Place the bottle with the nozzle directly over the crack.
- 3. Apply slight pressure to the bottle to release the crack repair solution.
- 4. Allow the solution to flow smoothly into the crack.
- 5. Wipe off excess solution from the surface.
- 6. Follow the recommended curing times for your specific application.

Technical Data	
Appearance:	Smooth, paste-like consistency
Odor:	Mild
Density:	1.2 g/cm ³
Solids Content:	85%
Viscosity:	8,000 - 10,000 cPs
Tack-Free Time:	Approximately 1 hour at 25°C
Full Cure Time:	24-48 hours at 25°C
Shore A Hardness:	80 (after full cure)
Tensile Strength:	2.5 MPa
Elongation at Break:	≥800%
Chemical Resistance:	Resistant to common household chemicals.
UV Resistance:	Resistant to UV exposure.
Mildew Resistance:	Excellent resistance to mildew growth.
Temperature Resistance:	It can withstand temperatures ranging from -20°C to 60°C.
Packing Information:	600 gm with an integrated nozzle applicator.
Coverage:	Approx 150 to 200 rft, depending on crack width and depth.
Shelf Life:	12 months at room temperature; proper storage extends product longevity.

