

Mega Glass Seal, your ultimate solution for preserving and protecting glass surfaces with a high bond seal that can withstand the harshest UV rays and weather conditions. Our innovative glass sealer is designed to provide unparalleled durability and long-lasting performance, making it the go-to choice for sealing glass in a variety of applications, including aluminum, steel, bronze, wood, and more.

KEY FEATURES:

Superior Adhesion and Waterproof Performance:

Mega Glass Seal's advanced formula ensures outstanding adhesion and water resistance. It creates a strong bond, making it ideal for glass-to-glass, glass-to-wood, glass-to-steel, and glass-to-bronze applications, while also preventing water infiltration.

Exceptional Durability:

Mega Glass Seal is engineered to resist cracking, shrinking, and color fading, ensuring that your materials maintain their strength and original appearance.

Versatile Adhesion for Multiple Materials:

This adhesive is compatible with a wide range of materials, including glass, wood, steel, and bronze, making it a versatile choice for all your projects.

Easy Application with Integrated Nozzle:

Mega Glass Seal sets itself apart with its innovative nozzle applicator. This built-in feature simplifies the application process. Just place the bottle's nozzle directly over the joint or surface, apply gentle pressure, and watch the adhesive flow smoothly and evenly.

Suitable for Indoor and Outdoor Use:

Whether you're working on interior or exterior projects, Mega Glass Seal provides reliable performance in various environments.

USAGE GUIDELINES:

- 1. Prepare the materials and ensure they are clean and free from debris.
- 2. Place the bottle with the nozzle directly over the joint or surface.
- 3. Apply slight pressure to the bottle to release the adhesive.
- 4. Allow the adhesive to flow smoothly into the joint or adhere to the surface.
- 5. Wipe off excess adhesive as needed.
- 6. Follow recommended curing times for your specific application.

Technical Data	
Appearance:	Smooth, paste-like consistency
Odor:	Mild
Density:	1.2 g/cm ³
Solids Content:	90%
Viscosity:	8,000 - 10,000 cPs
Tack-Free Time:	Approximately 2 hour at 25°C
Full Cure Time:	24-48 hours at 25°C
Shore A Hardness:	80 (after full cure)
Tensile Strength:	2.3 MPa
Elongation at Break:	450%
Chemical Resistance:	Resistant to common household chemicals
UV Resistance:	Resistant to UV exposure
Mildew Resistance:	Excellent resistance to mildew growth
Temperature Resistance:	It can withstand temperatures ranging from -20°C to 60°C
Packing:	Each bottle contains 600gm with an integrated nozzle applicator
Coverage:	150 to 200 rft, depending on application thickness and tile size.
Shelf Life:	12 months at room temperature; proper storage extends product longevity.



MEGA GLASS-SEAL