



Mega Sealers
Waterproofing Solutions

MEGA CLEAR GUARD

**CLEAR TRANSPARENT SINGLE COMPONENT
ACRYLIC BASED WATERPROOF COATING**



DESCRIPTION

MEGA CLEAR GUARD is a single component thermoplastic acrylic clear waterproof coating which has excellent colour, gloss retention and exterior durability properties. On drying it forms a transparent, hard, tough but flexible film.

FEATURES AND BENEFITS

- Excellent adhesion performance.
- High UV resistant, long life.
- Has abrasion and wear resistant.
- Single component, ready to use elastic material.
- Forms uniform structure without connection edges.
- Forms bright and easy to clean surface.
- Resistant to water and deicing salts.
- Suitable for pedestrian traffic after curing.
- Prevents color fading and dust formation on polyurethane waterproofing materials.

Typical Applications

1. Bathroom floor, kitchen floor, balcony, roof, wall, etc.
2. Concrete floor to stop water leaking as waterproof layer.
3. Interior walls, toilet floor, basement.
4. Swimming pool waterproofing

Application Procedure

Preparation of Substrate

The application surface must be dry, clean and free from all types of grease. All dust, loose and friable material must be completely removed from all surfaces before application of the product, preferably by brush and/or vacuum.

Application Method

Material is ready to use. After mix well the material, it should be applied roller (solvent resistant roller-non fuzzy roller), brush (thick haired brush) or sprayer (pressure: ~ 200 - 250 bar, nozzle: 0.38mm - 0.53mm, angle: ca. 50 - 80°). Layer thickness is recommended as 1 mm thickness. 3th coat application is recommended for better waterproofing and obtaining weather resistance. Layer thickness of system: approx. 0.6 mm. If necessary, additional coats can be applied. For a final layer thickness of 1.5 - 1.7 mm minimum 4 - 5 coats are required. The product can be over coated with itself.



Clean all equipment with clean water immediately after use



Store paint in dry conditions and protect from extreme temperatures.

TECHNICAL DATA

Form	Liquid
Appearance/Color	White (After Apply Transparent)
Packing	Bucket / Cane / Drum
Chemical base	Acrylic Base Polyurethane Liquid
Solid content	Approximately 70% ± 10%
Initial setting	3-5 hours
Final curing time	1-3 days (depending on ambient temperature/thickness)



MEGA CLEAR GUARD

Head Office: Plot No. C1-C, 2nd Floor, Main Khayaban-e-Itehad, Near KFC, Opposite Dubai Islamic Bank, DHA Phase 7, Karachi.

Plant: Plot B-653, Sector-3, Near Life Care Medical, Ahsanabad, Karachi.

Contact: +92 318 3880164 | +92 318 3880163

www.megasealers.com | info@megasealers.com | www.fb.com/Mega-Sealers