

PRODUCT DESCRIPTION

PANDA SEAL-760, the epitome of excellence in protective coatings. This single component acrylic based elastomeric coating is engineered to withstand the toughest of conditions, providing unparalleled durability and flexibility. Formulated with advanced technology, PANDA SEAL-760 offers seamless protection against moisture, UV rays, and environmental contaminants, ensuring long-lasting safeguarding for various surfaces.



Applications

Industrial: Seal roofs, walls, and floors against moisture and damage.

Commercial: Protect concrete, metal, or wood from UV rays and contaminants.

Residential: Coat decks, driveways, and foundations for durability.

Versatile: Ideal for concrete, metal, wood, and masonry.

Moisture guard: Prevent water damage in basements and walls.

UV shield: Shield surfaces exposed to sunlight, such as roofs and outdoor structures, from UV degradation and color fading.

Weatherproof: Withstand extreme weather conditions, including rain, snow, heat, and cold, ensuring reliable protection in any environment.

Methodology

Applying PANDA SEAL-760 is simple and efficient, requiring just a brush or roller. Begin by ensuring the surface is clean, dry, and free from any debris. Stir the coating thoroughly to achieve a consistent texture. Using a high-quality brush or roller, apply PANDA SEAL-760 evenly across the surface, working in manageable sections to ensure thorough coverage. For best results, apply two coats, allowing sufficient drying time between coats as per the manufacturer's instructions. Once applied, PANDA SEAL-760 dries rapidly, providing seamless protection for your surfaces.

A PRODUCT OF

